

REMARKS

This Preliminary Amendment cancels, without prejudice, claims 1 to 17 in the underlying PCT Application No. PCT/DE03/02314 and adds new claims 18 to 40. The new claims, inter alia, conform the claims to United States Patent and Trademark Office rules and does not add any new matter to the application.

In accordance with 37 C.F.R. § 1.125(b), the Substitute Specification (including the Abstract) contains no new matter. The amendments reflected in the Substitute Specification (including Abstract) are to conform the Specification and Abstract to United States Patent and Trademark Office rules or to correct informalities. As required by 37 C.F.R. §§ 1.121(b)(3)(ii) and 1.125(c), a Marked-Up Version of the Substitute Specification comparing the Specification of record and the Substitute Specification also accompanies this Preliminary Amendment. Approval and entry of the Substitute Specification (including Abstract) are respectfully requested.

The underlying PCT Application No. PCT/DE03/02314 includes an International Search Report, dated January 21, 2004, a copy of which is included. The Search Report includes a list of documents that were considered by the Examiner in the underlying PCT application.


It is respectfully submitted that the subject matter of the present application is new, non-obvious and useful. Prompt consideration and allowance of the application are respectfully requested.

Respectfully submitted,

KENYON & KENYON

Dated: Feb. 16, 2005

By:


Richard L. Mayer
Reg. No. 22,490
No. 42,194

One Broadway
New York, New York 10004
(212) 425-7200
CUSTOMER NO. 26646

[10191/3668]

METHOD AND DEVICE FOR FASTENING AND ALIGNING A SENSOR

~~Background Information~~

FIELD OF THE INVENTION

The present invention relates to a method and a device for fastening and aligning a sensor, especially e.g., a video sensor, on the windshield of a motor vehicle.

BACKGROUND INFORMATION

~~Today's motor~~ Motor vehicles are may be equipped with a plurality of sensors, such as ultrasound sensors or video sensors, in order, for example, to gather information about the surroundings of the motor vehicle. The fastening and aligning of these sensors on the vehicle deserve great importance, in this context, so that the functioning of the sensors may be ensured.

In particular, in motor vehicles, video sensors are used in larger numbers for gathering information on the surroundings. Stereo camera systems, for instance, are used for observing the road space located ahead of the motor vehicle, for object recognition or the measurement of distance from a preceding motor vehicle. In this context, in stereo camera systems two video sensors are used, which are positioned in such a way manner that they record essentially the same scene.

~~From German~~ Published Patent Application ~~10162652.5 of~~
~~12/20/2001, that was not prepublished, methods are known~~ No.
101 62 652.5 describes methods for fastening video sensors in the passenger compartment of a motor vehicle, the sensor being connected via a holding element to a support, especially the inner side of the windshield or the roof. ~~The~~ A disadvantage of these methods is that no precise mechanical alignment of

EV323019414

the sensors is undertaken. Especially in the case of stereo camera systems, the commonly recorded viewing angle of the video sensors determines the useful range of the system, since for the evaluation of the image information, overlapping image ranges of both video sensors are may be needed. The precise mechanical alignment of the video sensors, that is, the setting of the sensor axis, plays a decisive role here for the useful range of the stereo camera system and for the subsequent image processing.

In this context, the sensor axis is regarded as a preferred direction having a view of the measuring process. In a video sensor, the optical axis ~~is equivalent~~ corresponds to the sensor axis.

~~Summary of the Invention~~

SUMMARY

The method described below, for fastening and aligning a sensor via a holding element to a support, ~~has the advantage~~ may provide that a precise alignment of the sensor axis takes place in the nominal direction. In motor vehicles, stereo camera systems are used, for example, to gather information from the surroundings of the motor vehicle, the stereo camera systems being made up of two video sensors, which record essentially the same scene. To evaluate the image information, two overlapping image ranges of the two video sensors are may be required. The viewing angle of the two video sensors recorded in common defines, in this case, the ~~useful~~ range of the stereo camera system. Because of the precise alignment of the video sensors, the method described ~~here increases in an advantageous manner~~ herein may increase the useful range of the stereo camera system. In the case of stereo camera systems, the method described and the device ~~makes~~ may make possible ~~in an advantageous manner~~ the fastening and the precise alignment of the sensor axes of the

two video sensors relative to each other. ~~In particular, in an advantageous manner~~ **For example**, the setting of the sensor axes of the two video sensors is made possible ~~in such a way~~ that there is squinting **or strabismus** of the video sensors. In this context, the recorded range of the stereo camera system is placed closer to the motor vehicle during installation in the motor vehicle.

By reworking the sensor seating surface, the method described in the following and the device **may** make possible ~~in a particularly advantageous manner~~ the fastening and alignment of at least one sensor, ~~particularly e.g.,~~ in motor vehicles. ~~In an advantageous manner, the~~ **The** precise alignment of the sensor axis of the at least one sensor ~~is~~ **may be** achieved by the determination using measuring techniques of the deviation of the sensor axis from the nominal direction by the surveying of the sensor seating surface and the subsequent reworking.

In ~~one variant of the method~~ **an example embodiment**, by the use of at least one video sensor, the deviation of the sensor axis from the nominal direction is determined by temporarily not installing the at least one video sensor in the holding element that has not been reworked. By determining the deviation by methods of image processing, such as by calibrating methods in a calibrating field, ~~in this variant, in an especially advantageous manner,~~ the manufacturing tolerances of the support and/or the holding element and/or the sensor seating surface and/or the video sensor are determined, and are compensated for during subsequent reworking.

In ~~one further variant~~ **an example embodiment**, a carrier is used to which the support is connected. The carrier is a part of the reworking device. The relative position of the support and the holding element with respect to the reworking device

is determined by the use of the carrier. The reworking device makes possible the reworking of the sensor seating surface by material-removing reworking methods, ~~preferably e.g.,~~ milling, drilling ~~and or~~ and/or laser processing. ~~In an especially advantageous manner, in this variant of the method described, the, etc.~~ The previous measurement of the deviation of the sensor axis from the nominal direction may be omitted, because the position of the support is directly determined by the connection of the support to the carrier. This ~~makes~~ may make possible the cost-effective carrying out of the method, since costly measuring units for determining the deviation of the sensor axis from the nominal direction ~~are~~ may not be necessary.

~~In an advantageous manner, the~~ The method for fastening and aligning various sensor types, such as ultrasound sensors, light-sensitive sensors, video sensors or sensors for electromagnetic radiation may be used. The only assumption is that the sensors have a sensor axis.

~~It is of advantage that the~~ The method is may be able to be used with convex, concave and/or level surfaces of the support. The method described and the device ~~are especially advantageous~~ may be provided for fastening and aligning sensors, ~~preferably e.g.,~~ video sensors, at the windshield of a motor vehicle. Windshields in motor vehicles have a curved surface. Because of the molding process during manufacturing of the windshield, the curvature demonstrates a wide divergence. The holding element often also has component part tolerances, which result in deviation of the sensor axis from the nominal direction. If there are component part tolerances of the windshield and/or the holding element, the method ~~leads~~ may lead to precise alignment of the sensor axis in the nominal direction ~~in an advantageous manner.~~

~~In an advantageous manner, the~~ The method may be used with any nominal direction of the sensor axis. The method ~~is~~ particularly may be suitable if the sensor axis points in the direction of the holding element and the support, or in the opposite direction.

During aligning of the sensor axis to the holding element and the support, the support and/or the holding element have to be transparent to the quantities influencing the sensor. ~~In an advantageous manner, the~~ The transparency for the sensor-influencing quantities may also be achieved by material-removing processing methods.

~~It is also of advantage that the~~ The method ~~is~~ may be able to be applied in conjunction with the use of an adhesion process for fastening the holding element to the support. ~~In an especially advantageous method, the~~ The precise alignment of the sensor may be carried out at the same time as the hardening of the adhesive, by reworking the sensor seating surface. This ensures may ensure a rapid performance of the fastening of the holding element, and the accurate alignment of the sensor axis may take place at the same time.

~~Especially when~~ When the method described is used for fastening video sensors to the inside of the windshield of a motor vehicle, the method described ~~leads~~ may lead to time and cost saving, because the two method steps may be carried out in parallel.

~~In an advantageous manner, the~~ The reworking of the sensor seating surface by various material-removing processing methods, preferably e.g., milling, drilling and/or laser processing, etc., may take place depending on the type and the properties of the material used for the holding element.

~~In a particularly advantageous manner, the~~ The method described ~~makes~~ may make possible the aligning of the sensor with respect to its rotation about the sensor axis, by mounting a centering pin receptacle. ~~It is advantageous in this regard that mounting~~ Mounting the centering pin receptacle ~~is~~ may be able to take place during the reworking of the holding element, and that because of that no additional method step ~~is~~ may be required. This ~~ensures~~ may ensure a rapid and cost-effective execution of the method.

~~In one variation of the method, the~~ The accommodation ~~is~~ may be protected by a cover element for a part of the sensor and/or the sensor antechamber, during the reworking of the sensor seating surface, from the intrusion of chips and other contaminations. ~~Particularly when~~ When one is installing video sensors, this ~~leads in an advantageous manner~~ may lead to a better image quality, because the optical path of the images ~~is~~ may not be disturbed by soiling. ~~In an advantageous way this leads~~ This may lead to an extension of the useful life of the sensors, since otherwise, for example, remaining diluted soluble oil ~~is~~ or cutting oil may be able to lead to corrosion of the sensor and/or the holding element.

The device described below for fastening and aligning a sensor, via a holding element, to a support ~~has the advantage~~ may provide that, during the reworking of the sensor seating surface for the alignment of the sensor in the nominal direction, the accommodation ~~does~~ may not have to be changed. This ~~leads~~ may lead to an execution of the method that saves time and costs, since an additional processing of the holding element ~~is~~ may not be necessary. It ~~is of advantage~~ may be provided that the sensor seating surface may be reworked by using an oversize, and the accommodation ~~is~~ may be larger than the part of the sensor to be accommodated, because of the use of the oversize.

~~In an advantageous way, the~~ **The** device ~~is~~ **may be** designed in such a way that the sensor antechamber is bigger than the angular coverage of the sensor. This ~~makes~~ **may make** reworking the sensor's antechamber, while processing the sensor seating surface, unnecessary. This ~~leads~~ **may lead** to an execution of the method described that saves time and costs.

~~In one variation~~ **an example embodiment** of the device, with the sensor installed, the accommodation and the sensor antechamber are sealed from the surroundings by a sealing ring. ~~In particular, when~~ **When** using a video sensor, this ~~leads in an advantageous manner~~ **may lead** to a reduction of soiling of the sensor during operation, and thereby to an improvement of the image quality.

~~Further advantages result from~~ **aspects are set for the below** ~~in~~ the following description of exemplary embodiments with reference to the figures, and from the dependent claims **appended Figures**.

~~Brief Description of the Drawings~~

~~The present invention is explained in detail below, in light of the specific embodiments represented in the drawing. The figures show:~~

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 ~~the~~ **is a** side view of a device for fastening and aligning a sensor before the reworking of the sensor seating surface, .

Figure 2 ~~the~~ **is a** top view of a device for fastening and aligning a sensor before the reworking of the sensor seating surface, .

Figure 3 ~~the~~ is a side view of a device for fastening and aligning a sensor after the reworking of the sensor seating surface₇ .

Figure 4 ~~the~~ is a top view of a device for fastening and aligning a sensor after the reworking of the sensor seating surface₇

Figure 5 ~~the~~ is a side view of a device having a cover element during the reworking using a milling head₇ .

Figure 6 ~~the representation of~~ illustrates a device having a centering pin receptacle and a centering pin for aligning the sensor.

~~Description of Exemplary Embodiments~~

DETAILED DESCRIPTION

Figures 1 and 2 show the side view and the top view of a device for fastening and aligning a sensor 13, 23, in ~~the preferred~~ an exemplary embodiment a video sensor, before the reworking of sensor seating surface 14, 24. The support 11, 21, on which video sensor 13, 23 is mounted, is the windshield of a motor vehicle. Video sensor 13, 23 is connected via a holding element 12, 22 to the support 11, 21. The connection of video sensor 13, 23 to holding element 12, 22 is made via seating surface 14, 24. Holding element 12, 22, in ~~the preferred~~ an exemplary embodiment, has a cylindrical accommodation 16, 26 for a part of video sensor 13, 23. Sensor antechamber 15, 25 is used as a baffle, for the reduction of interfering, stray pick-up light. In Figures 1 and 2, the deviation of sensor axis 18, 28 from the nominal direction 19, 29 is ~~drawn in~~ illustrated. In ~~the preferred~~ an exemplary embodiment, sensor axis 18, 28 is determined by the optical axis of the video sensor 13, 23. In ~~the preferred~~ an

exemplary embodiment, nominal direction 19, 29 is determined relatively with respect to the axis of travel of the motor vehicle. Nominal direction 19, 29 is determined with respect to the axis of travel by ~~preferably~~ , e.g., two angles, such as the vertical pitch angle and the horizontal yaw angle. In the first variant of ~~the preferred~~ an exemplary embodiment, for example, nominal direction 19, 29 is parallel to the axis of travel, whereas in the second variant the nominal direction is tilted vertically with respect to the axis of travel.

In the first method step, holding element 12, 22 is connected to support 11, 21, for example, by an adhesion process. In ~~the preferred~~ an exemplary embodiment, holding element 12, 22 is located on the inside of a motor vehicle's windshield. Holding element 12, 22 is fastened close to the inner rearview mirror, so as simultaneously to lie in the wiped area of the windshield and to impair the view of the driver as little as possible.

In a first variant of ~~the preferred~~ an exemplary embodiment, after hardening of the adhesive, in the next method step, the deviation of sensor axis 18, 28 from nominal direction 19, 29 is determined by measurement techniques. ~~Preferably, the~~ The deviation of sensor axis 18, 28 from the nominal direction 19, 29 ~~is~~ may be ascertained indirectly by measuring sensor seating surface 14, 24. The measurement is made in this case by optical and/or mechanical measuring methods, such as probes. Alternatively, in a second variant of ~~the preferred~~ an exemplary embodiment, temporary installation of video sensor 13, 23 in non-reworked holding element 12 is possible. ~~Preferably, the~~ The deviation of sensor axis 18, 28 from the nominal direction 19, 29 ~~is~~ may be ascertained indirectly by measuring sensor seating surface 14, 24. In this context, the deviation is ascertained by the method of image processing.

In a further variant of the preferred an exemplary embodiment, the ascertainment of the deviation of sensor axis 18, 28 from nominal direction 19, 29 by measuring techniques ~~is~~ may not be necessary. Rather, in this variant, support 11, 21, ~~in the preferred exemplary embodiment~~ the windshield, is fastened using a carrier which is a part of the reworking device. The carrier determines the relative position of support 11, 21 and of holding element 12, 22 with respect to the reworking device. This makes possible a direct reworking, without previous measuring of the deviation of sensor axis 18, 28 from nominal direction 19, 29.

In the following method step, reworking of sensor seating surface 14, 24 is carried out, for instance, on the basis of the deviation ascertained. To rework holding element 12, 22 that has been produced by die-casting technology, various material-removing processing methods, preferably e.g., milling, drilling and/or laser processing, etc., may be used.

In the last method step, video sensor 13, 23 is connected to holding element 12, 22 via reworked sensor seating surface 14, 24. For the connection, various methods may be used, especially e.g., adhesion, screw connection or snap-in techniques, etc. Sealing ring 17, 27 is used for sealing accommodation 16, 26 and sensor antechamber 15, 25 of holding element 12, 22 from the surroundings of the device, particularly e.g., during operation of video sensor 13, 23.

Figures 3 and 4 show the side view and the top view of a device for fastening and aligning a sensor 33, 43 after processing sensor seating surface 34, 44. Holding element 32, 42 is connected to support 31, 41. Sensor axis 38, 48 is aligned in nominal direction 39, 49.

~~In the preferred exemplary embodiment, accommodation~~
Accommodation 36, 46 ~~is~~ may be dimensioned by an oversize ~~in~~
~~such a way~~ that it is able to accommodate the tilting of video
sensor 33, 43 after processing of sensor seating surface 34,
44 in diameter and depth. Sensor antechamber 35, 45 is
established as a conical opening ~~in such a way~~ that, after the
processing of sensor seating surface 34, 44, the angular
coverage of video sensor 33, 43 is not restricted by the walls
of sensor antechamber 35, 45. Sealing ring 37, 47 makes
possible the sealing of the inner space of holding element 32,
42 after processing of sensor seating surface 34, 44, sealing
ring 37, 47 being formed ~~in such a way~~ that in the case of
tilting of video sensor 33, 43, sealing ~~is~~ may be ensured.
Holding element 32, 42 is formed ~~in such a way~~ that processing
of sensor seating surface 34, 44 is possible when holding
element 32, 42 is connected to support 31, 41. At the same
time, sensor seating surface 34, 44 is dimensioned ~~in such a~~
~~way~~ that the function and stability of holding element 32, 42
is not impaired by reworking. This ~~is preferably~~ may be
achieved by fixing an oversize.

Figure 5 shows a variant of ~~the~~ an exemplary embodiment. In
the reworking of sensor seating surface 56 of holding element
52 which is connected to support 51, a cover element 53
protects the inner space of holding element 52 from the
intrusion of chips and/or dirt because of the processing of
sensor seating surface 56, ~~particularly~~ e.g., by cutting head
55. Seal 54 ~~ensures~~ may ensure the waterproof and dirt-tight
sealing of the inner space.

Figure 6 shows holding element 61 having a centering pin
receptacle 63 and centering pin 64 for aligning sensor 62, a
video sensor in ~~the preferred~~ an exemplary embodiment, about
sensor axis 65. Minimizing the rotation of video sensor 62
about sensor axis 65 ~~is~~ may be necessary, for example, in

order to obtain good image quality. During the reworking of sensor seating surface 66, applying centering pin receptacle 63 is possible in the same method step. The alignment of video sensor 62 is performed by centering pin 64. In ~~one~~ improved an example embodiment, the use of two or more centering pin receptacles 63 and centering pins 64 ~~is~~ may be possible.

The method described and the device are not limited to the fastening and alignment of video sensors 13 on the windshield of motor vehicles. The method and the device are suitable for all sensor types that have a sensor axis 18, ~~especially e.g.,~~ ultrasound sensors, light-sensitive sensors, video sensors and/or sensors for electromagnetic radiation, such as radar radiation, such as radar sensors, etc. ~~Especially~~ For example, in the case of ultrasound sensors or sensors for electromagnetic radiation, sensor axis 18 is defined by the central axis of the radiation lobe. In ~~the preferred~~ an exemplary embodiment in the motor vehicle, nominal direction 19 in ultrasound sensors is also defined relative to the axis of travel. It is possible, for instance, to connect a plurality of sensors 13 of the same and/or various types to a support 11 via a holding element 12. This variant of the method permits the simultaneous, precise fastening and alignment of a plurality of sensors 13 via one holding element 12. The only assumption is that holding element 12 has a sensor seating surface 14, for each sensor 13, which is able to be reworked. ~~In particular, the~~ The method described and the device may make possible the fastening and the alignment of two video sensors which ~~essentially~~ record the same scene, ~~especially e.g.,~~ stereo camera systems. In this context, the video sensors may be connected to support 11, either via a single holding element 12 having two sensor seating surfaces 14, or via two holding elements 12 each having one sensor seating surface 14. As the support, using convex, concave

and/or flat surfaces, etc., is possible for accommodating holding element 12. Support 11 and/or holding element 12 may have component part tolerances which are compensated for by the method and the device. The alignment of sensor axis 18 of sensor 13 is as desired. ~~Preferably~~ For example, there is alignment with support 11 and holding element 12, or the opposite. Other methods than adhesion processes are possible for connecting holding element 12 to support 11. ~~Especially~~ For example, in the case of supports 11 made of metal or plastic, detachable or non-detachable connections such as screws or rivets are ~~conceivable~~ possible.

In ~~one further variant of the~~ an example embodiment, holding elements 12 without accommodation 16 and/or sensor antechamber are possible. In this variant ~~of the embodiment~~, sensor 13 is fastened directly to sensor seating surface 14.

If an accommodation 16 and/or a sensor antechamber 15 is present, their shape will depend on the properties of sensor 13. The shape of accommodation 16 ~~has~~ may have to be adapted to the geometrical properties of sensor 13, whereas sensor antechamber 15 has to correspond to the angular coverage of sensor 13. The geometrical properties of sensor seating surface 14 ~~must~~ may also correspond to the sensor type, ~~in particular~~ e.g., a planar or point-shaped sensor seating surface 14 may be present. The material of support 11 and/or of holding element 12 ~~has~~ may have to be partially or completely transparent to the sensor-influencing variables because of the material properties, and/or the transparency to the sensor-influencing variables is achieved by material-removing processing methods. In ~~the~~ an exemplary embodiment, the windshield, which is made of glass, is partially transparent to light in the visible range, whereas the transparency of holding element 12 ~~was~~ is achieved by an opening in the form of sensor antechamber 15.

In ~~one variant of the~~ an exemplary embodiment ~~described~~, the determination of the deviation of sensor axis 18 from nominal direction 19 and/or the reworking of sensor seating surface 14 are carried out during the hardening of the adhesive in the adhesion process for connecting holding element 12 to support 11. This procedure ~~is~~ may be suitable for all connections of holding element 12 to support 11 that require a longer time to reach the final fastness.

In ~~one additional variant of the~~ an exemplary embodiment ~~described~~, it is ~~conceivable~~ possible that one may change the sequence of the individual method steps. For example, it is possible first to determine the deviation of sensor axis 18 from nominal axis 19, then to rework sensor seating surface 14 on account of the ascertained deviation of sensor axis 18 from nominal direction 19, so that one may subsequently connect holding element 12 to support 11. In the last method step, sensor 13 is ~~finally~~ connected to holding element 12. Alternatively, even after the reworking, fastening sensor 13 to holding element 12 and subsequently fastening holding element 12, having sensor 13 on it, to support 11 is possible.

~~Abstract~~

ABSTRACT

A method and a device are ~~proposed~~ **provided** for fastening and aligning a sensor ~~(13)~~, particularly **, e.g.,** in motor vehicles, the sensor ~~(13)~~ being connected to a support ~~(11)~~ via a holding element ~~(12)~~. By reworking the sensor seating surface ~~(14)~~, a precise alignment of the sensor axis ~~(18)~~ with the nominal direction ~~(19)~~ ~~is~~ **may be** achieved.

~~(Figure 1)~~